



SUPER-DRY

F SERIES | Mini Filters and Desiccant Dryers | ●●●

PROTECT YOUR COMPRESSED AIR APPLICATION

- FILTER SEPARATOR (FS)
- COALESCER FILTER (FC)
- DESICCANT DRYER (FD)



Specifications and ordering information:

Model	Air Flow @	Inlet/Outlet NPT	Dimensions			Weight	Replacement Kit
	100 psig scfm		A	B	C		
FC-½	20	½	3 ⅞	7 ½	6 ½	1.2	EFC-½
FC-1	40	1	3 ⅞	11 ⅞	10	3.8	EFC-1
FD-½	20	½	3 ⅞	7 ½	6 ½	1.2	EFD-½
FD-1	40	1	3 ⅞	11 ⅞	10	3.8	EFD-1
FS-½	20	½	3 ⅞	7 ½	6 ½	1.2	EFS-½
FS-1	40	1	3 ⅞	11 ⅞	10	3.8	EFS-1

FS/FC/FD-½: Maximum inlet temperature: 100°F (38°C) Maximum inlet pressure: 130 psig Plastic Bowl

FS/FC/FD-1: Maximum inlet temperature: 100°F (38°C) Maximum inlet pressure: 150 psig Metal Bowl

Drainage: FS (float drain) FC/FD (manual drain)

