

SUPER-DRY

F Series | Mini Separators, Filters and Desiccant Dryers |

Protect your compressed air application



- High efficiency
- Portable and lightweight
- Continuous clean dry air



SUPER-DRY

F Series | Mini Separators, Filters and Desiccant Dryers

The Super-Dry F Series contains:

- A coalescer filter (FC) designed to filter water, oil and other contaminants
- A miniature desiccant dryer (FD) to remove moisture from your compressed air system
- A filter separator (FS) designed to separate water droplets and evacuate them with a float drain

Quick change replacement kit



FC / FD Series elements



FD element



FC element



FS float drain



FS deflector

Specifications and ordering information:

Model	Air Flow @ 100 psig scfm	Inlet/Outlet NPT in	Dimensions			Weight lbs	Replacement Kit
			A	B	C		
FC-1/2	20	1/2	3 1/8	7 1/2	6 1/2	1.2	EFC-1/2
FC-1	40	1	3 5/8	11 7/8	10	3.8	EFC-1
FD-1/2	20	1/2	3 1/8	7 1/2	6 1/2	1.2	EFD-1/2
FD-1	40	1	3 5/8	11 7/8	10	3.8	EFD-1
FS-1/2	20	1/2	3 1/8	7 1/2	6 1/2	1.2	EFS-1/2
FS-1	40	1	3 5/8	11 7/8	10	3.8	EFS-1

FS/FC/FD-1/2: Maximum inlet temperature: 100°F (38°C) Maximum inlet pressure: 130 psig Plastic Bowl

FS/FC/FD-1: Maximum inlet temperature: 100°F (38°C) Maximum inlet pressure: 150 psig Metal Bowl

Drainage: FS (float drain) FC / FD (manual drain)

